Toolwell[™]

Tel: (800) 786-6112

Fax: (866) 332-3299

www.Toolwell.com

Email: info@toolwell.com



360° Maneuverability • Non-floor-damaging wheels

Model CC3

Load Capacity:

3 tons each -or-12 tons Set of 4 Mix & Match as Needed!

Each dolly sold separately

«









Included	One dolly with non floor marking JUWAmid wheels
Load Capacity for Each Dolly	3 tons 6,000 lbs
Load Capacity combined for Set of 4 (each dolly sold separately)	12 tons 24,000 lbs
Floor Condition	For Level Floor
Height	4.3"
Dolly Dimensions (Length x Length x Width)	22.2" x 22.5" x 4.72"
Wheel Dimensions (Ø x Width)	3.3" x 1.6"
Number of Wheels	3x3
Mounting hole	0.51" x 3.1"
Weight	84 lbs
Manufacturer • MPN	JUNG • RS 3 T



JUWAmid Wheels with Dual Ball Bearings

- Will not damage or mark sensitive floors.
- Specially designed for turning in place (reduced rubber-effect on floors) for easy change of direction.
- Low rolling resistance and low break out resistance.
- Narrow wheels can rotate in opposite directions for easy turning.

For use on level floors only

WARNING! Not for uneven floors. Unequal weight distribution may occur resulting in overloading. Not for declining floors due to runaway load risk.

Free lifetime rigging & technical support. Entire parts available.



