

Model D3



DIRECTIONAL DOLLY

Advanced high-strength steel dolly
with non floor damaging wheels

Zigzag Maneuverability • Non Floor Damaging Wheels

Load Capacity:

**3 tons each -or-
12 tons Set of 4**

» Mix & Match
as Needed! «



**Common Configuration
Set of 4**

12 tons Set Capacity

Each dolly sold separately

For use on level floors only

Included	One dolly with non floor marking JUWathan wheels
Load Capacity for Each Dolly	3 tons 6,000 lbs
Load Capacity combined for Set of 4 (each dolly sold separately)	12 tons 24,000 lbs
Floor Condition	For Level Floor
Height (from Floor to Top of Load Pad)	5.9"
Dolly Dimensions (Width x Length)	16.5" x 16.1"
Wheel Dimensions (Ø x Width)	3.3" x 1.7"
Number of Wheels	8
Supporting Surface (w/ Anti-Slip Load Pad)	Ø 5.9"
Weight	55 lbs
Manufacturer • MPN	JUNG • JLF 3.5



**JUWathan Wheels with
Dual Ball Bearings**

- Patented wheel material is baked in an oven over long period for elasticity & extreme toughness
- Will not damage or mark sensitive floors.
- Elastic material can overcome small obstacles and keep on rolling.
- Narrow wheels can rotate in opposite directions for easy turning.

Optional Accessories



**Pulling Handle
with Towing Eye**
Length: 47"

Connecting Bar
1-part: Length: 47"
2-part: Length: 94"

Capacity Rating
Dolly built to meet or exceeds ASME B30.1.

WARNING! Not for uneven floors. Unequal weight distribution may occur resulting in overloading or slipping of dollies. Not for declines due to runaway load risk.

Free lifetime rigging & technical support. Entire parts available.



MADE IN GERMANY

By JUNG



5 Year Manufacturer's Warranty

(damage due to overloading not covered)