

## Model D5

# DIRECTIONAL DOLLY

Advanced high-strength steel dolly  
with non floor damaging wheels

**Zigzag Maneuverability • Non Floor Damaging Wheels**

Load Capacity:

**5 tons** each -or-  
**20 tons** Set of 4



» Mix & Match  
as Needed! «



**Common Configuration  
Set of 4**

**20 tons** Set Capacity

Each dolly sold separately

**For use on level floors only**

Included	One dolly with non floor marking JUWathan wheels
Load Capacity for Each Dolly	5 tons   10,000 lbs
Load Capacity combined for Set of 4 (each dolly sold separately)	20 tons   40,000 lbs
Floor Condition	For Level Floor
Height (from Floor to Top of Load Pad)	5.9"
Dolly Dimensions (Width x Length)	16.5" x 16.1"
Wheel Dimensions (Ø x Width)	3.3" x 1.7"
Number of Wheels	12
Supporting Surface (w/ Anti-Slip Load Pad)	Ø 5.9"
Weight	62 lbs
Manufacturer • MPN	JUNG • JLF 5



**JUWathan Wheels with  
Dual Ball Bearings**

- Patented wheel material is baked in an oven over long period for elasticity & extreme toughness
- Will not damage or mark sensitive floors.
- Elastic material can overcome small obstacles and keep on rolling.
- Narrow wheels can rotate in opposite directions for easy turning.

## Optional Accessories



**Pulling Handle  
with Towing Eye**  
Length: 47"

**Connecting Bar**  
1-part: Length: 47"  
2-part: Length: 94"

**Capacity Rating**  
Dolly built to meet or exceeds ASME B30.1.

**WARNING!** Not for uneven floors. Unequal weight distribution may occur resulting in overloading or slipping of dollies. Not for declines due to runaway load risk.

Free lifetime rigging & technical support. Entire parts available.



**MADE IN GERMANY**

By JUNG



**5 Year Manufacturer's Warranty**

(damage due to overloading not covered)