Tel: (800) 786-6112

Fax: (866) 332-3299

www.Toolwell.com

Email: info@toolwell.com





Functionality

- ▶ **Thin:** Diamond plated loading plate.
- All-in-one: Lift load. Roll load. Steer load.
- Polyurethane rollers: Protect your floors.
- Rolls easily: Large diameter rollers outfitted with ball bearings.
- Application range: Ideal to move industrial cabinets, vaults, boxes or cube shaped machines.

Lifting Dollies

Lift and roll cube shaped loads

Model LD1.8

Set Capacity: 1.8 tons (3950 lbs)

(i) Included: Set of 2 dollies plus two tie down straps.

Includes	2 dollies and 2 tie-down straps
Set Capacity	1.8 tons (3950 lbs)
Lift height	7.1 inches
Nose plate depth	2 inches
Nose plate thickness	0.15 inches (4mm)
Retracted height	39.6 inches
Width	21.3 inches
Length of tie down straps	16 ft each
Roller diameter	5.9 inches
Set Weight	165 lbs
Manufacturer • MPN	JUNG • JHT1.8

How to use

- 1. Position one dolly on each side of the load.
- 2. Push nose plates under load.
- 3. Strap together to hold in place.
- 4. Pump each unit to lift up load.
- 5. Now roll.
- 6. Turn by turning handles. Side-by-side rollers are automatically kept in parallel.

Free lifetime rigging & technical support!



