



110V Electric pumps operate multiple jacks simultaneously

## HYDRAULIC ELECTRIC PUMPS

For remote operation of jacks



### Model P5

with 2 Nozzles



### Model P30

with 2 Nozzles



### Model P30-4

with 4 Nozzles

<b>Operates JUNG Jacks</b>	Any TWO <b>5 and 10 ton</b> jacks	Any TWO <b>5, 10, 15, 20 and 30 ton</b> jacks	Any FOUR <b>5, 10, 15 and 20-ton</b> jacks
<b>Usable Oil Volume</b>	33.3 fl.oz. (0.26 Gallons)	162 fl.oz. (1.3 gallons)	162 fl.oz. (1.3 gallons)
<b>Flow Rate</b> (no load   full load)	66.5   5.5 fl.oz. / min	132   11.1 fl.oz. / min	132   11.1 fl.oz. / min
<b>Working Pressure, Motor</b>	7540 psi, 110/115V, 0.25HP	7540 psi, 110/115V, 0.5HP	7540 psi, 110/115V, 0.5HP
<b>Dimensions L x W x H</b>	13 x 7.8 x 8"	9.5 x 11.5 x 18.5 "	9.5 x 11.5 x 18.5 "
<b>Weight</b>	20 lbs	84 lbs	90 lbs
<b>Manufacturer • MPN</b>	JUNG • JPE 5	JUNG • JPE 30 NVR	JUNG • JPE 30-4 NVR

- ▶ Each pump outfitted with 2-4 separate nipples to **operate 1 single jack to 4 jacks** simultaneously.
- ▶ Fittings are **no-drip quick connectors**

- ▶ **One oil circuit for 2 to 4 jacks**
- ▶ P30 and P30-4 with **pressure gauge** and **cable remote control** (9ft)

**WARNING!** For synchronous lifting of two jacks connected to one pump, each jack must carry equal weight. **Use one pump per jack if weight is not equally divided for independent control of each jack.**

## HYDRAULIC HOSE

Drip free connectors, oil filled



Model	H6	H9	H12	H39	H..
Length	6 ft	9 ft	12 ft	39 ft	custom

Free lifetime rigging & technical support hotline!