

ROTATING DOLLY

360° Maneuverability • Non-floor-damaging wheels

Model R1.5

Load Capacity:

1.5 tons each -or-
6 tons Set of 4



» Mix & Match
as Needed! «



Common Configuration
Set of 4

6 tons Set Capacity

Each dolly sold separately

For use on level floors only



JUWAmid Wheels with
Dual Ball Bearings

- Will not damage or mark sensitive floors.
- Specially designed for turning in place (reduced rubber-effect on floors) for easy change of direction.
- Low rolling resistance and low break out resistance.
- Narrow wheels can rotate in opposite directions for easy turning.

| | |
|--|---------------------------------------|
| Included | One dolly with non floor marking JUWA |
| Load Capacity for Each Dolly | 1.5 tons 3,000 lbs |
| Load Capacity combined for Set of 4 (each dolly sold separately) | 6 tons 12,000 lbs |
| Floor Condition | For Level Floor |
| Height (from Floor to Top of Load Pad) | 4.3" |
| Dolly Dimensions (Width x Length) | 19.5" x 20.8" |
| Wheel Dimensions (∅ x Width) | 3.3" x 1.6" |
| Number of Wheels | 3x2 |
| Supporting Surface (w/ Anti-Slip Load Pad) | ∅ 5.9" |
| Weight | 44 lbs |
| Manufacturer • MPN | JUNG • JKB 1.5 K |

Optional Accessories



Pulling Handle with Towing Eye

Length: 47"



Connecting Bar

1-part: Length: 47"
2-part: Length: 94"

Capacity Rating

Dolly built to meet or exceeds ASME B30.1.

WARNING!

Not for uneven floors. Unequal weight distribution may occur resulting in overloading or slipping of dollies. Not for declines due to runaway load risk.

Free lifetime rigging & technical support. Entire parts available.



MADE IN GERMANY

By JUNG



5 Year Manufacturer's Warranty

(damage due to overloading not covered)