Toolwell[™]

Tel: (800) 786-6112

Fax: (866) 332-3299

www.Toolwell.com

Email: info@toolwell.com



360° Maneuverability • Non-floor-damaging wheels



Model R10

Load Capacity:

10 tons each -or-40 tons Set of 4



| Included | One dolly with non floor marking JUWAthan wheels |
|------------------------------------------------------------------|--------------------------------------------------|
| Load Capacity for Each Dolly | 10 tons 20,000 lbs |
| Load Capacity combined for Set of 4 (each dolly sold separately) | 40 tons 80,000 lbs |
| Floor Condition | For Level Floor |
| Height (from Floor to Top of Load Pad) | 7.1" |
| Dolly Dimensions (Width x Length) | 38.4" x 26.2" |
| Wheel Dimensions (Ø x Width) | 5.5" x 2.3" |
| Number of Wheels | 4x2 |
| Supporting Surface (w/ Anti-Slip Load Pad) | Ø 9.8" |
| Weight | 313 lbs |
| Manufacturer • MPN | JUNG • JKB 10 G |

For use on level floors only



JUWAthan+ Wheels with Aluminum Core and Dual Ball Bearings

- Larger wheels ensure easy turning and rolling.
- Superior JUWAthan material provides ultimate floor protection for heavier loads.
- Elastic material offers higher reliability under toughest conditions.
- Narrow wheels can rotate in opposite directions for easy turning.

Optional Accessories



Capacity Rating

Dolly built to meets or exceeds ASME B30.1.

warning! Not for uneven floors. Unequal weight distribution may occur resulting in overloading or slipping of dollies. Not for declines due to runaway load risk.

Free lifetime rigging & technical support. Entire parts available.



