Tel: (800) 786-6112

Fax: (866) 332-3299

www.Toolwell.com

Email: info@toolwell.com



360° Maneuverability • Non-floor-damaging wheels

Model R4

Load Capacity:

4 tons each -or-16 tons Set of 4



Included	One dolly with non floor marking JUWAmid wheels
Load Capacity for Each Dolly	4 tons 8,000 lbs
Load Capacity combined for Set of 4 (each dolly sold separately)	16 tons 32,000 lbs
Floor Condition	For Level Floor
Height (from Floor to Top of Load Pad)	4.3"
Dolly Dimensions (Width x Length)	18.7" x 27"
Wheel Dimensions (Ø x Width)	3.3" x 1.6"
Number of Wheels	4x3
Supporting Surface (w/ Anti-Slip Load Pad)	Ø 9.8"
Weight	95 lbs
Manufacturer - MPN	JUNG • JKB 4 K

For use on level floors only



JUWAmid Wheels with Dual Ball Bearings

- Will not damage or mark sensitive floors.
- Specially designed for turning in place (reduced rubber-effect on floors) for easy change of direction.
- Low rolling resistance and low break out resistance.
- Narrow wheels can rotate in opposite directions for easy turning.

Optional Accessories



Pulling Handle with Towing Eye Length: 47"



1-part: Length: 47" 2-part: Length: 94"

Capacity Rating

Dolly built to meets or exceeds ASME B30.1.

warning! Not for uneven floors. Unequal weight distribution may occur resulting in overloading or slipping of dollies. Not for declines due to runaway load risk.

Free lifetime rigging & technical support. Entire parts available.



