Tel: (800) 786-6112

Fax: (866) 332-3299

www.Toolwell.com

Email: info@toolwell.com



360° Maneuverability • Non-floor-damaging wheels



Model R6

Load Capacity:

6 tons each -or-24 tons Set of 4



One dolly with non floor Included marking JUWAmid wheels **Load Capacity for Each Dolly** 6 tons | 12,000 lbs Load Capacity combined for Set of 4 24 tons | 48,000 lbs (each dolly sold separately) Floor Condition For Level Floor Height (from Floor to Top of Load Pad) 4.3" Dolly Dimensions (Width x Length) 20.7" x 27.2" Wheel Dimensions (Ø x Width) 3.3" x 1.7" Number of Wheels 4x4 Supporting Surface (w/ Anti-Slip Load Pad) Ø 9.8" Weight 97 lbs Manufacturer • MPN JUNG • JKB 6 K

For use on level floors only



JUWAmid Wheels with Dual Ball Bearings

- Will not damage or mark sensitive floors.
- Specially designed for turning in place (reduced rubber-effect on floors) for easy change of direction.
- Low rolling resistance and low break out resistance.
- Narrow wheels can rotate in opposite directions for easy turning.

Optional Accessories



Pulling Handle with Towing Eye Length: 47"

Connecting Bar

1-part: Length: **47**"

2-part: Length: 94"

Capacity Rating

Dolly built to meets or exceeds ASME B30.1.

warning! Not for uneven floors. Unequal weight distribution may occur resulting in overloading or slipping of dollies. Not for declines due to runaway load risk.

Free lifetime rigging & technical support. Entire parts available.



