

SYNCHRONIZED LIFTING SYSTEM

For JUNG Toe Jacks

System Capacity: 40 tons

Synchronizes four 10-ton jacks

Model **SLS40**



Includes:

- Synchronized Lifting System (**SLS40**)

Model **SLS40 Kit**



Includes:

- Synchronized Lifting System (**SLS40**)
- 4 Jacks (**EX10**)
- 4 Hoses (**H39**)

FUNCTIONALITY

► Synchronized Lift System

Raise and lower four jacks independently or simultaneously. Cable remote (Lift / Hold), precise gentle lowering control, w pressure gauge, overload protection sensors, no-drip hydraulic quick connectors.

► Toe Jack

Toe is adjustable to various starting positions. Swivel feet firmly support the jack to prevent tipping. Patented slide shoe design counterbalances torque of forward leaning.

► Hose

No-drip quick connectors

Sync Lifting System **SLS40**

Number of Jack Nozzles	4
Lift Capacity TOTAL	40 tons 80,000 lbs
Lift Capacity PER JACK	10 tons 20,000 lbs
Working pressure	7540 psi
Pump type	Electric hydraulic
Motor Specs	110V / 50 Hz / 1 Phase
H x L x W	39.3" x 56.8" x 25.9"
Weight ready for use	520 lbs
Pump oil volume	256 fl.oz. (2 Gallons)
Manufacturer • MPN	JUNG • JD 40 E+VS 110V

Hydraulic Toe Jack **EX10**

Lift Capacity (each jack)	10 tons 20,000 lbs
Number of adjustable toe starting positions	5
Toe height at lowest starting position	0.6"
Toe height at highest starting position	7.1"
Stroke (maximum lift from starting position)	5.9"
Toe depth (usable)	2.2"
H x L x W	12.1 x 10.6 x 9.7"
Weight ready for use	64 lbs
Oil volume	10.1 fl.oz.
Manufacturer • MPN	JUNG • JH 10 Ex

Hose **H39**



Length	39 feet
Manufacturer • MPN	JUNG • JS 12

Optional: Shorter hoses available



MADE IN GERMANY

By JUNG



1 Year Manufacturer's Warranty*

* on All Electrical Products (5 Year on all other)

(damage due to overloading not covered)