

## Synchronized Lifting System

For JUNG Toe Jacks (sold separately)

### Model **SLS80**

Set Capacity: **80 Tons**

Powers: **Four 20-Ton Jacks**



**For loads with uneven weight distribution.**

### Functionality

- ▶ Raise and lower four jacks independently or simultaneously.
- ▶ Cable remote (Lift / Hold)
- ▶ Precise gentle lowering control.
- ▶ Cage protects entire unit from damage.
- ▶ With pressure gauge
- ▶ Overload protection sensors.
- ▶ No-drip hydraulic quick connectors.

**Alert!** Pulls up to 27 Amps at start-up under full load so **requires 30 Amp outlet.**

Lift Capacity	<b>80 tons</b> 160,000 lbs
Capacity per jack	20 tons 40,000 lbs
Working pressure	7540 psi
Pump type	Electric hydraulic
External dimensions in Cage H x L x W	34.2" x 50.5" x 20.1"
Weight ready for use	535 lbs
Pump oil volume	320 fl.oz. (2.5 Gallons)
Motor Specs	110V / 50 Hz / 1 Phase
Manufacturer • MPN	JUNG • JD 80 E+VS 110V

### Jacks and Hoses Sold Separately

Designed for use with four EX20 jacks. Compatible with other JUNG jacks but not recommended.

### Hydraulic Toe Jack **EX20**

Capacity per jack: 20 tons



### Hose **H32**



The jacks come standard with 9ft hoses. Longer 32ft hoses are optional. Mix and match hose length to fit load size.

Free lifetime rigging & technical support hotline!



**MADE IN GERMANY**  
By JUNG



**5 Year Manufacturer's Warranty\***  
\* 1 Year Warranty on All Electrical Products  
(damage due to overloading not covered)