
# **Toolwell**<sup>™</sup>

Tel: (800) 786-6112

Fax: (866) 332-3299

www.Toolwell.com

Email: info@toolwell.com



\( \begin{align\*} \text{Load capacity of 4-point skate} \)
system is reduced when Center of Gravity (CG) location is not centered.




## TANDEM MACHINE SKATES

Advanced high-strength steel skates with non floor damaging wheels

**Load Capacity:** 

12 tons each -or-24 tons combined





### Model T12

Steerable Adjustable-width

Model B12

Adjustable-Width Rear

Included	One steerable 2-part skate with non floor marking wheels, connecting bars & pulling handle.	One straight-line 2-part skate with non floor marking wheels and connecting bar.
Load Capacity each skate model	12 tons / 25,000 lbs	12 tons / 25,000 lbs
Load Capacity combined T12 + B12 ()*	24 tons / 50,000 lbs	
Load Capacity each load cassette (each loading point)	6 tons / 12,500 lbs	6 tons / 12,500 lbs
Dimensions without bars (height x width x length)	4.3" x 17.5" x 39.4" each skate part	4.3" x 15" x 13" each skate part
Load Wheel Dimensions (Ø x width)	3.3" x 3.3"	3.3" x 3.3"
Supporting Surface (each with anti-slip load pad)	Ø 5.9"	6.9" x 6.7"
Adjustable Length of Connecting Bar	26.0" – 52.8"	48.4"
Weight	229 lbs	77 lbs
Manufacturer • MPN	JUNG • JTLB 14 K	JUNG • JFB 12 K

#### Free lifetime rigging & technical support hotline!



#### Patented wheel material is baked in oven over long period for elasticity and extreme toughness!

Non floor roug damaging For fl

Non floor marking

For smooth and rough floors

For floors with cracks and dirt

For both inside and outside use

Overcomes small obstacles easily by molding around them to keep rolling.

No stop, up & over action required like with other wheels.

Low floor pressure

Low break out & low rolling resistance

Low push-pull force and low manpower requirements Shock absorbent

Reliable under toughest working conditions Superior performance and durability over traditional polyurethane, composite or steel wheels



