



HYDRAULIC HAND PUMPS

For operating 1 jack, or 2 jacks simultaneously



Model P26

- ▶ **Precise lowering control**
- ▶ **Overload protection valve**
- ▶ **Fast lift speed**
- ▶ **Quick connectors** for drip free hydraulic hose connection
- ▶ **Foot plate** to hold pump in place

Oil Volume	67.6 fl.oz (0.5 Gallons)
Flow Rate (no load full load)	0.45 0.08 fl.oz. / pump
Working Pressure	7540 psi / 520 bar
Hose Connections	2
External Dimensions L x W x H	30.3 x 6.7 x 6.6"
Weight (ready for use)	29 lbs
Manufacturer ▪ MPN	JUNG ▪ JP26

Operates Any One or Two **5 or 10 Ton** JUNG Jack(s):



ⓘ Operation with 15 and 20 ton jacks is not recommended because of high number of pump strokes required.)

WARNING! For synchronous lifting of two jacks connected to one pump, each jack must carry equal weight. **Use one pump per jack if weight is not equally divided for independent control of each jack.**

HYDRAULIC HOSE

Drip free connectors, oil filled



Model	H6	H9	H12	H15	H..
Length	6 ft	9 ft	12 ft	15 ft	custom

Free lifetime rigging & technical support hotline!



MADE IN GERMANY
By JUNG



5 Year Manufacturer's Warranty
(damage due to overloading not covered)