



Electric pumps operate 1 or 2 jacks simultaneously

HYDRAULIC ELECTRIC PUMPS

For remote operation of jacks



Model P5



Model P30

Operates JUNG Jacks	Any TWO 5 and 10 ton jacks	Any TWO 5, 10, 15, 20 and 30 ton jacks And ONE 50 tons jack
Oil Volume	33.8 fl.oz. (0.37 Gallons)	257 fl.oz. (2 gallons)
Flow Rate (no load full load)	64.2 3.4 fl.oz. / min	132 11.1 fl.oz. / min
Working Pressure, Motor	7540 psi, 110/115V, 0.25HP	7540 psi, 110/115V, 0.5HP
Dimensions L x W x H	13 x 7.8 x 8"	9.5 x 11.5 x 18.5"
Weight	20 lbs	63 lbs
Manufacturer • MPN	JUNG • JPE 5	JUNG • JPE 30 NVR

- ▶ Each pump outfitted with 2 separate nipples to **operate 1 single jack or 2 jacks** simultaneously.
- ▶ Fittings are **no-drip quick connectors**
- ▶ **One oil circuit for 2 jacks**
- ▶ P30 and P50 with **pressure gauge** and cable **remote control** (9ft)

WARNING! For synchronous lifting of two jacks connected to one pump, each jack must carry equal weight. **Use one pump per jack if weight is not equally divided for independent control of each jack.**

HYDRAULIC HOSE

Drip free connectors, oil filled



Model	H6	H9	H12	H15	H..
Length	6 ft	9 ft	12 ft	15 ft	custom

Free lifetime rigging & technical support hotline!