Tel: (800) 786-6112

Fax: (866) 332-3299

www.Toolwell.com Email: info@toolwell.com

# CONFINED SPACE TOE JACKS

For use with an external pump

#### Model C10 Set 1 Model C10 Set 2



Set Capacity: 10 Tons

Set Capacity: 20 Tons

One 10 ton jack with one 9 ft. hose & a hand pump

Two 10 ton jacks with two 9 ft. hoses & a hand pump



## **Upgrade Option** C10 Set 1E and C10 Set 2E

Replace hand pump with 110V electric pump

### **Functionality**















- Use with feet in front or feet rotated to back
- Lift with toe or head
- Use vertically for lifting and horizontally for pushing
- Pumps outfitted with 2 drip free quick connection nipples to operate 1 or 2 jacks simultaneously.
- Hydraulic jacks and pumps operate at 7540 psi. (Do not use with 10,000 psi pumps)

#### WARNING!

For synchronous lifting of two jacks connected to one pump, each jack must carry equal weight. Use one pump per jack if weight is not equally divided.

# **Hydraulic Toe Jack C10**



Lift Capacity each jack	<b>10 tons</b> 20,000 lbs
Toe height	0.8"
Maximum lift (stroke)	10.2"
Toe width (narrow tip) x depth	2.4 x 2"
Dimensions H x L x W, feet in <b>front</b>	14.6 x <b>8.0</b> x 7.9"
Dimensions H x L x W, feet in <b>back</b>	14.6 x <b>10.2</b> x 7.9"
Diameter top cylinder	2.9"
Oil volume	17 fl.oz.
Weight ready for use	39 lbs
Manufacturer • MPN	JUNG • JHS 10

## **Hand Pump P26**



Flow rate per pump (loaded)	0.08 fl.oz./pump
Oil volume	67.6 fl.oz.
Dimensions L x W x H	30.3 x 6.7x 6.6"
Weight ready for use	29 lbs
Manufacturer • MPN	JUNG • JP 26

# 1/4 HP Electric Pump P5



Flow rate per minute (loaded)	3.4 fl.oz. / min
Oil volume	33.8 fl.oz.
Dimensions L x W x H	13 x 7.8 x 8"
Weight ready for use	20 lbs
Manufacturer • MPN	JUNG • JPE 5

### Hose H9



Free lifetime rigging & technical support hotline!



