

PUMP OPERATED TOE JACKS

With advanced lifting and lowering functionality

Model

EX20 Set 1

Set Capacity: **20 Tons**



One 20 ton jack with one 9 ft. hose & electric pump

Model


EX20 Set 2

Set Capacity: **40 Tons**



Two 20 ton jacks with two 9 ft. hoses & electric pump

Functionality



- ▶ Toe is adjustable to various starting positions.
- ▶ Swivel feet firmly support the jack to prevent tipping.
- ▶ Lift with toe or lift with top loading plate
- ▶ Patented slide shoe design counterbalances torque of forward leaning.
- ▶ Pumps outfitted with 2 connection nipples to operate 1 or 2 jacks simultaneously.
- ▶ Hydraulic jacks and pumps operate at 7540 psi. (Do not use with 10,000 psi pumps)

WARNING!

For synchronous lifting of two jacks connected to one pump, each jack must carry equal weight. **Use one pump per jack if weight is not equally divided.**

Free lifetime rigging & technical support hotline!

Hydraulic Toe Jack EX20



Lift Capacity (each jack)	20 tons 40,000 lbs
Number of adjustable toe starting positions	5
Toe height at lowest starting position	0.8"
Toe height at highest starting position	8.8"
Stroke (maximum lift from starting position)	7.5"
Toe depth (usable)	2.6"
External dimensions H x L x W	13.4x14.2x12.7"
Oil volume	24.7 fl.oz.
Weight ready for use	132 lbs
Manufacturer • MPN	JUNG • JH 20 Ex

½ HP Electric Pump P30



Flow rate (loaded)	11.1 fl.oz. / min
Oil volume	257 fl.oz. (2 gal)
Dimensions L x W x H	9.5 x11.5 x18.5"
Motor	½ HP 110V
Weight ready for use	88 lbs
Manufacturer • MPN	JUNG • JPE 30

Hose H9



Length	9 feet
Manufacturer • MPN	JUNG • JS 3



MADE IN GERMANY

By JUNG



5 Year Manufacturer's Warranty*

* 1 Year Warranty on All Electrical Products

(damage due to overloading not covered)