

## PUMP OPERATED TOE JACKS

With advanced lifting and lowering functionality

### Model

#### EX30 Set 1

Set Capacity: **30 Tons**



One 30 ton jack with one 9 ft. hose & electric pump

### Model


#### EX30 Set 2

Set Capacity: **60 Tons**



Two 30 ton jacks with two 9 ft. hoses & electric pump

### Functionality



- ▶ Toe is adjustable to various starting positions.
- ▶ Swivel feet firmly support the jack to prevent tipping.
- ▶ Lift with toe or lift with top loading plate
- ▶ Patented slide shoe design counterbalances torque of forward leaning.
- ▶ Pumps outfitted with 2 connection nipples to operate 1 or 2 jacks simultaneously.
- ▶ Hydraulic jacks and pumps operate at 7540 psi. (Do not use with 10,000 psi pumps)

### WARNING!

For synchronous lifting of two jacks connected to one pump, each jack must carry equal weight. **Use one pump per jack if weight is not equally divided.**

Free lifetime rigging & technical support hotline!

### Hydraulic Toe Jack EX30



Lift Capacity (each jack)	<b>30 tons</b> 60,000 lbs
Number of adjustable toe starting positions	5
Toe height at lowest starting position	0.8"
Toe height at highest starting position	12.2"
Stroke (maximum lift from starting position)	8.0"
Toe depth (usable)	2.6"
External dimensions H x L x W	16.5 x15.0 x14.8"
Weight ready for use	203 lbs
Oil volume	42.9 fl.oz.
Manufacturer • MPN	JUNG • JH 30 Ex

### ½ HP Electric Pump P30



Flow rate (loaded)	11.1 fl.oz. / min
Oil volume	257 fl.oz. (2 gal)
Dimensions L x W x H	9.5 x11.5 x18.5"
Motor	½ HP 110V
Weight ready for use	88 lbs
Manufacturer • MPN	JUNG • JPE 30

### Hose H9



Length	9 feet
Manufacturer • MPN	JUNG • JS 3



**MADE IN GERMANY**

By JUNG



**5 Year Manufacturer's Warranty\***

\* 1 Year Warranty on All Electrical Products

(damage due to overloading not covered)