Tel: (800) 786-6112

Fax: (866) 332-3299

www.Toolwell.com

Email: info@toolwell.com

# **CONFINED SPACE TOE JACKS**

For use with an external pump



## **Functionality**



- Tall with long stroke, Narrow, Low profile toe
- Use with feet in front or feet rotated to back
- Lift with toe or head
- Use vertically for lifting and horizontally for pushing
- Pumps outfitted with 2 drip free quick connection nipples to operate 1 or 2 jacks simultaneously.
- Hydraulic jacks and pumps operate at 7540 psi. (Do not use with 10,000 psi pumps)

### **WARNING!**

For synchronous lifting of two jacks connected to one pump, each jack must carry equal weight. **Use one pump per jack if weight is not equally divided.** 

## Hydraulic Toe Jack S10



Lift Capacity each jack	<b>10 tons</b> 20,000 lbs
Number of toe starting positions	5
Toe height at lowest / highest start position	0.8" / 7.1"
Stroke (max lift from start position)	4.25"
Toe width (narrow tip) x Toe depth	2.4" x 2.2"
Dimensions H x L x W, feet in <b>front</b>	10.4 x <b>8.1</b> x 7.9"
Dimensions H x L x W, feet in <b>back</b>	10.4 x <b>10.2</b> x 7.9"
Weight ready for use	51 lbs
Oil volume	7 fl.oz.
Manufacturer • MPN	JUNG • JHS10ku

### Hand Pump P26



	•
Flow rate per pump (loaded)	0.08 fl.oz./pump
Oil volume	67.6 fl.oz.
Dimensions L x W x H	30.3 x 6.7x 6.6"
Weight ready for use	29 lbs
Manufacturer • MPN	JUNG • JP 26

## 1/4 HP Electric Pump P5



Flow rate per minute (loaded)	3.4 fl.oz. / min
Oil volume	33.8 fl.oz.
Dimensions L x W x H	13 x 7.8 x 8"
Weight ready for use	20 lbs
Manufacturer • MPN	JUNG • JPE 5

### Hose H9



Length 9 feet

Manufacturer • MPN JUNG • JS 3

Free lifetime rigging & technical support hotline!



