

Tel: (800) 786-6112

Fax: (866) 332-3299


www.Toolwell.com
Email: info@toolwell.com

Skate: **A60/B60**

WEIGHT DISTRIBUTION ON FLOOR

For machine skate models A60 (JLB 60H) and B60 (JFB 60H)

Wheel Footprint



Wheel size

F • ► length: 6.7" | 170mm H • ► length: 3.3" | 85mm F&H • ► diameter: 7.9" | 200mm


Wheel contact surface with floor

F • ▶ width: 1.58" | 40mm F • ▶ length: 6.70" | 170mm H • ▶ width: 1.97" | 50mm H • ▶ length: 3.35" | 85mm

Footprint per wheel:

F• ► **10.59** in² | 68cm² **H**• ► **6.60** in² | 42.5cm²

Skate Footprint



Footprint per skate: ▶ 137.52 in²


Skate Model **B60**



Footprint per skate: ▶ 137.52 in²

Footprint per ft²

Maximum footprint within any 1 ft² area



1 ft² area

Footprint per ft²:

• ► 37.91 in²

Variations in Footprint:

With increasing weight, the elastic JUWAthan wheel material spreads out and increases the contact area with the floor. The enlarged footprint divides the weight over a larger area so that the pressure onto the floor is drastically reduced. The footprint above is measured at maximum load capacity. (1) The size of the actual footprint and in turn the actual psi may vary based on actual load weight, temperature, load bearing duration, etc.. Therefore the data provided is an estimate to be used as a general guideline only.

Pressure per in² for concerns about indenting soft floor

Pressure (psi) = Load weight (lbs) per skate

Footprint (in²) per skate

Pressure per in² at maximum load capacity • ▶ 960 psi

Pressure per ft² for concerns about breaking through supported floor

Pressure (psf) = Load weight (lbs) per skate x Footprint (in²) per ft²

Footprint (in²) per skate

Pressure per one ft² at maximum capacity ▶ 36,388 psf