

Tel: (800) 786-6112

Fax: (866) 332-3299

www.Toolwell.com


Email: info@toolwell.com

Skate: **AP15/B15**

WEIGHT DISTRIBUTION ON FLOOR

For machine skate models AP15 (JLA-p 15/30G) and B15 (JFB 15G)





Wheel size

F • ► length: 2.3" | 118mm H • ► length: 2.3" | 59mm F&H • ► diameter: 5.5" | 140mm


Wheel contact surface with floor

F • ➤ width: 1.30" | 33mm F • ➤ length: 2.32" | 118mm H • ➤ width: 0.85" | 22 mm H • ➤ length: 2.32" | 59mm

Footprint per wheel:

F• ▶ **3.02** in² | 38.9cm² **H•** ▶ **1.95** in² | 12.6cm²

Skate Footprint



Footprint per skate: ▶ 39.72 in²

Skate Model **B15**


Skate Model



Footprint per skate: • > 36.24 in²

Footprint per ft²

Footprint within 1 ft² area with the highest pressure



1 ft² area

Footprint per ft²:

• > 18.12 in²

Variations in Footprint:

The yellow JUWAthan wheel is elastic and spreads out under weight. This gives the wheel a larger footprint for traction. The black JUWAmid wheel is harder to help carry the weight and provide improved turning characteristics. (1) The footprint above is measured at maximum load capacity. The size of the actual footprint and in turn the actual psi may vary based on actual load weight, temperature, load bearing duration, etc.. Therefore the data provided is an estimate to be used as a general guideline only.

Pressure per in² for concerns about indenting soft floor

Pressure (psi) = Load weight (lbs) per skate

Footprint (in²) per skate

Max pressure per in² at maximum load capacity • ► 827 psi

Pressure per ft² for concerns about breaking through supported floor

Pressure (psf) = Load weight (lbs) per skate x Footprint (in²) per ft²

Footprint (in²) per skate

Pressure per one ft² at maximum capacity ▶ 15,000 psf