Tel: (800) 786-6112

Fax: (866) 332-3299

www.Toolwell.com Email: info@toolwell.com


Dolly:

**R2** 

## WEIGHT DISTRIBUTION ON FLOOR

For rotating dolly model R2 (JKB 2K)

## Wheel Footprint



Wheel size Length: **1.7"** | 43mm Diameter: 3.3" | 85mm


Wheel contact surface with floor

Width: 0.18" | 4.5mm Length: 1.70" | 43mm

## Footprint per wheel:

• **0.31 in<sup>2</sup>** | 1.94cm<sup>2</sup>

**Dolly Footprint** 




## Footprint per dolly:

• **1.86 in<sup>2</sup>** | 11.64cm<sup>2</sup>

Footprint per ft<sup>2</sup>

Maximum footprint within any 1 ft<sup>2</sup> area



Footprint per ft<sup>2</sup>:

• **0.62 in<sup>2</sup>** | 3.88cm<sup>2</sup>

Characteristics of wheel material in relation to footprint:

The JUWAmid wheel material is formulated to easily turn in place and to provide a high degree of maneuverability at a low rolling resistance.

The harder wheels are therefore designed to produce a minimal footprint to reduce the "rubber"effect during turns.

If a larger footprint is desired, please consider using JUNG machine skates with elastic JUWAthan+ wheels.

Pressure per in<sup>2</sup> for concerns about indenting soft floor

Load weight (lbs) per dolly Pressure (psi) = -Footprint (in<sup>2</sup>) per dolly

Pressure per in<sup>2</sup> at maximum load capacity >> 2,150 psi

Pressure per ft<sup>2</sup> for concerns about breaking through supported floor

Load weight (lbs) per dolly x Footprint (in²) per ft² Pressure (psf) =  $\frac{1}{2}$ Footprint (in<sup>2</sup>) per dolly

Pressure per one ft<sup>2</sup> at maximum capacity • > 1,333 psf

1 The size of the actual footprint and in turn the actual floor pressure is influenced by various factors such as temperature and load bearing duration. Therefore, the data provided is an estimate to be used as a general guideline only.

