

Tel: (800) 786-6112

Fax: (866) 332-3299


www.Toolwell.com Email: info@toolwell.com

Skate: T30/B30

## WEIGHT DISTRIBUTION ON FLOOR

For tandem machine skate model T30 (JTLB 30G) and B30 (JFB 30G)

## **Wheel Footprint**



#### Wheel size

- ► length: 2.3" | 59mm
- ► diameter: 5.5" | 140mm

#### Wheel contact surface with floor

- ▶ width: 1.30" | 33mm
- ► length: 2.32" | 59mm


## Footprint per wheel:

• **3.02 in<sup>2</sup>** | 19.47cm<sup>2</sup>

# **Skate Footprint** Skate Model T30 Skate Model **B30** Footprint per skate: ► 72.48 in<sup>2</sup>

#### Footprint per ft<sup>2</sup>

Maximum footprint within any 1 ft2 area



1 ft<sup>2</sup> area

**Footprint** per ft<sup>2</sup>:

• > 31.53 in<sup>2</sup>

#### **Variations in Footprint:**

With increasing weight, the elastic JUWAthan wheel material spreads out and increases the contact area with the floor. The enlarged footprint divides the weight over a larger area so that the pressure onto the floor is drastically reduced. The footprint above is measured at maximum load capacity. (1) The size of the actual footprint and in turn the actual psi may vary based on actual load weight, temperature, load bearing duration, etc.. Therefore the data provided is an estimate to be used as a general guideline only.

### Pressure per in<sup>2</sup> for concerns about indenting soft floor

Pressure per in<sup>2</sup> at maximum load capacity • ► 827 psi

Pressure per ft<sup>2</sup> for concerns about breaking through supported floor

Load weight (lbs) per skate x Footprint (in<sup>2</sup>) per ft<sup>2</sup> Pressure (psf) = Footprint (in²) per skate

Pressure per one ft<sup>2</sup> at maximum capacity > 26,100 psf