

Tel: (800) 786-6112

Fax: (866) 332-3299


www.Toolwell.com Email: info@toolwell.com

Dolly: X30/Y30

WEIGHT DISTRIBUTION ON FLOOR

For container dolly model X30 (JTLB 30G+TL) and Y30 (JFB 30G+TL)





Wheel size

- ► length: 2.3" | 59mm
- ► diameter: 5.5" | 140mm

Wheel contact surface with floor

- ▶ width: 1.30" | 33mm
- ► length: 2.32" | 59mm


Footprint per wheel:

• **3.02 in²** | 19.47cm²

Dolly Footprint Dolly Model X30 Dolly Model **Y30** Footprint per dolly: ▶ 72.48 in²

Footprint per ft²

Maximum footprint within any 1 ft2 area



1 ft² area

Footprint per ft²:

• > 31.53 in²

Variations in Footprint:

With increasing weight, the elastic JUWAthan wheel material spreads out and increases the contact area with the floor. The enlarged footprint divides the weight over a larger area so that the pressure onto the floor is drastically reduced. The footprint above is measured at maximum load capacity. (1) The size of the actual footprint and in turn the actual psi may vary based on actual load weight, temperature, load bearing duration, etc.. Therefore the data provided is an estimate to be used as a general guideline only.

Pressure per in² for concerns about indenting soft floor

Load weight (lbs) per dolly Pressure (psi) = -Footprint (in²) per dolly

Pressure per in² at maximum load capacity • ► 827 psi

Pressure per ft² for concerns about breaking through supported floor

Load weight (lbs) per dolly x Footprint (in2) per ft2 Pressure (psf) = Footprint (in²) per dolly

Pressure per one ft² at maximum capacity > 26,100 psf