

Optional Accessories:

Each roller and each accessory sold separately

Swivel Tops



with
padded top

Turning Handle



BÖRKEY ROLLERS

with NYLON wheels



Model series KP

MPN: N-PA6 Series

Model	Capacity (tons)	Capacity (kN)	L x W (inches)	Height without top with (inches)	Wheel diameter (inches)	Total number of wheels	Wheels under stress	Weight Roller Top (lbs)
KP #2	6	60	8.7 x 4.4	3.0 4.6	0.9	13	4	16 8
KP #3	10	100	10.6 x 5.1	3.6 5.5	1.2	13	4	29 12

Use

- ▶ For concrete floors
- ▶ Machinery moving & material handling
- ▶ On-off loading
- ▶ Short distance travel

Features:

- ▶ Nylon wheels for floor protection on concrete
- ▶ Non-Mounted and Versatile
- ▶ Low-profile or turnable with swivel tops

Roller Construction:

- ▶ Solid interlocking carbon steel frame construction
- ▶ Nylon wheels on steel chain

Corrosion Resistance:

Zinc-phosphate coated frame for basic corrosion resistance.

Max speed: 16 ft/min

Applications:

Used as toolset by machinery movers for machine installation, maintenance and repair, when rollers are loaded and off-loaded frequently and when loads are rolled over short distances. For rolling on smooth concrete or asphalt.

Ease of Rolling:

Larger diameter wheels roll more easily than smaller wheels. Select roller size accordingly.

Capacity:

When using 4 or more rollers, load may rock on uneven surface, increasing load weight applied to any roller. Therefore, select suitable rated roller capacity carefully.

Precautionary measures must be taken for use on inclines to avoid run-away loads!

When mixing and matching rollers (or different load supports), keep the load at same loading height. Otherwise, rollers will tip and become point-loaded.