## Toolwell<sup>™</sup>

Tel: (800) 786-6112

Fax: (866) 332-3299

#### www.Toolwell.com

Email: info@toolwell.com



360° Maneuverability • Non-floor-damaging wheels



### Model R14

**Load Capacity:** 

14 tons each -or-56 tons Set of 4



Included	One dolly with non floor marking JUWAthan wheels
Load Capacity for Each Dolly	14 tons   28,000 lbs
Load Capacity combined for Set of 4 (each dolly sold separately)	56 tons   112,000 lbs
Floor Condition	For Level Floor
Height (from Floor to Top of Load Pad)	7.1"
Dolly Dimensions (Width x Length)	38.4" x 28.7"
Wheel Dimensions (Ø x Width)	5.5" x 2.3"
Number of Wheels	4x3
Supporting Surface (w/ Anti-Slip Load Pad)	Ø 9.8"
Weight	351 lbs
Manufacturer • MPN	JUNG • JKB 14 G

#### For use on level floors only



# JUWAthan+ Wheels with Aluminum Core and Dual Ball Bearings

- Larger wheels ensure easy turning and rolling.
- Superior JUWAthan material provides ultimate floor protection for heavier loads.
- Elastic material offers higher reliability under toughest conditions.
- Narrow wheels can rotate in opposite directions for easy turning.

#### **Optional Accessories**



#### **Capacity Rating**

Dolly built to meets or exceeds ASME B30.1.

warning! Not for uneven floors. Unequal weight distribution may occur resulting in overloading or slipping of dollies. Not for declines due to runaway load risk.

Free lifetime rigging & technical support. Entire parts available.



