

CONFINED SPACE TOE JACKS

For use with an external pump



Hydraulic Toe Jack S10

Lift Capacity each jack	10 tons 20,000 lbs
Number of toe starting positions	5
Toe height at lowest / highest start position	0.8" / 7.1"
Stroke (max lift from start position)	4.25"
Toe width (narrow tip) x Toe depth	2.4" x 2.2"
Dimensions H x L x W, feet in front	10.4 x 8.1 x 7.9"
Dimensions H x L x W, feet in back	10.4 x 10.2 x 7.9"
Weight ready for use	51 lbs
Oil volume	7 fl.oz.
Manufacturer • MPN	JUNG • JHS10ku

Hand Pump P26



Flow rate per pump (loaded)	0.08 fl.oz./pump
Oil volume	67.6 fl.oz.
Dimensions L x W x H	30.3 x 6.7x 6.6"
Weight ready for use	29 lbs
Manufacturer • MPN	JUNG • JP 26

1/4 HP Electric Pump P5



Flow rate per minute (loaded)	3.4 fl.oz. / min
Oil volume	33.8 fl.oz.
Dimensions L x W x H	13 x 7.8 x 8"
Weight ready for use	20 lbs
Manufacturer • MPN	JUNG • JPA 5

Hose H9



Length	9 feet
Manufacturer • MPN	JUNG • JS 3

Model S10 Set 1
Set Capacity
10 Tons

Model S10 Set 2
Set Capacity
20 Tons



One 10 ton jack with one 9 ft. hose & a hand pump


Two 10 ton jacks with two 9 ft. hoses & a hand pump



Upgrade Option "E"

Replace hand pump with ¼ HP electric pump 110V

Functionality



- ▶ Tall with long stroke, Narrow, Low profile toe
- ▶ Use with feet in front or feet rotated to back
- ▶ Lift with toe or head
- ▶ Use vertically for lifting and horizontally for pushing
- ▶ Pumps outfitted with 2 drip free quick connection nipples to operate 1 or 2 jacks simultaneously.
- ▶ Hydraulic jacks and pumps operate at 7540 psi. (Do not use with 10,000 psi pumps)

WARNING!

For synchronous lifting of two jacks connected to one pump, each jack must carry equal weight. **Use one pump per jack if weight is not equally divided.**

Free lifetime rigging & technical support hotline!



MADE IN GERMANY

By JUNG



5 Year Manufacturer's Warranty*

* 1 Year Warranty on All Electrical Products
(damage due to overloading not covered)