



## HYDRAULIC HAND PUMPS

For operating 1 jack, or 2 jacks simultaneously



### Model P26

- ▶ **Precise lowering control**
- ▶ **Overload protection valve**
- ▶ **Fast lift speed**
- ▶ **Quick connectors** for drip free hydraulic hose connection
- ▶ **Foot plate** to hold pump in place

<b>Oil Volume</b>	67.6 fl.oz (0.5 Gallons)
<b>Flow Rate</b> (no load   full load)	0.45   0.08 fl.oz. / pump
<b>Working Pressure</b>	7540 psi / 520 bar
<b>Hose Connections</b>	2
<b>External Dimensions L x W x H</b>	30.3 x 6.7 x 6.6"
<b>Weight</b> (ready for use)	29 lbs
<b>Manufacturer</b> • MPN	JUNG • JP26

Operates Any One or Two **5 or 10 Ton** JUNG Jack(s):



ⓘ Operation with 15 and 20 ton jacks is not recommended because of high number of pump strokes required.)

**WARNING!** For synchronous lifting of two jacks connected to one pump, each jack must carry equal weight. **Use one pump per jack if weight is not equally divided for independent control of each jack.**

### HYDRAULIC HOSE

Drip free connectors, oil filled



Model	H6	H9	H12	H15	H..
Length	6 ft	9 ft	12 ft	15 ft	custom

Free lifetime rigging & technical support hotline!



**MADE IN GERMANY**  
By JUNG



**5 Year Manufacturer's Warranty**  
(damage due to overloading not covered)